

PDM/PLM with HELiOS

Version 2023

System and Hardware Requirements

Date of issue: 05/10/2023




TOC

Architecture / System Overview.	
HELIOS Database Server	5
HELIOS Vault Server	5
HELIOS Client	5
HELiOS Internet Server	5
HELiOS Spooler	
License Server	
System and Hardware Requirements.	8
Important Notes!	
Discontinuation of "old" interfaces.	
System Requirements for the HELiOS Database Server	9
System Requirements for the HELiOS Vault Server	10
System Requirements for the HELiOS Client	11
Compatibility Matrix for Interfaced Applications (HELiOS).	12
System Requirements for the HELiOS Internet Server	15
System Requirements for the HELiOS Spooler	17
System Requirements for the License Server.	18
Operation in Virtual Environments	19
HELiOS Client	19
HELiOS Spooler.	19
License Server.	19
Network licenses on Virtual Machines (VM).	
Multiple HELiOS Servers on One Computer	20
Network Requirements	21
Daaluus	20

Architecture / System Overview

HELiOS is the PDM/PLM system for safe corporate processes. Typical use cases for PDM/PLM are:

- Central and safe management of all company-relevant documents.
- Company-wide access to product-related information via a locally installed HELiOS Client or, if desired, also without additional Client installation via the HELiOS Internet Server.
- Bringing in of external partners and suppliers as well as mobile employees via the HELiOS Internet Server.
- Company-wide control, output and conversion of drawings and documents via the HELiOS Spooler.
- Data exchange across departments with ERP systems via Standard Connectors or, if desired, as cus-tomer-specific solution.



HELIOS – **PDM/PLM** for the entire enterprise

To ensure that you actually work with the suitable hardware and software when using HELiOS, we recom-mend reading the information about the different HELiOS components contained in this Whitepaper. These are:

- HELiOS Database Server
- HELiOS Vault Server
- HELiOS Client
- HELiOS Internet Server
- HELiOS Spooler and
- License Server.

HFLiOS Database Server

HELiOS manages all metadata centrally in one database. For this a Database Server is required that supports and provides the corresponding data management services. You can use a Microsoft SQL Server as Database Server (RDBMS).

HFLiOS Vault Server

HELIOS saves all utilized data (files) either to a central file system or, if desired, to the HELIOS Vault Server. Whether a HELIOS Vault Server is required also depends on the interfaces types that that are used.

The HELiOS Vault Server is an "electronic safe" for all documents in a company that prevents an immediate, uncontrolled access to security-relevant files.

Special authentication and check-in/check-out mechanisms in the background efficiently restrict access to the persons who actually have access permission, while regulating simultaneous concurrent accesses on the basis of the corresponding access type.

Furthermore, the HELiOS Vault Server provides the basis for document replication when multiple locations are involved.

HELiOS Client

HELiOS can be used integrated in a CAD system such as HiCAD, but also as a standalone system – the so-called HELiOS Desktop. The corresponding Client must be installed locally.

HFLiOS Internet Server

Via a HELiOS Internet Server with Web Sharing you can give your customers and suppliers web-based access to projects, documents and articles. With the help of a common Internet Browser the corresponding infor-mation can be displayed, complete with graphical previews. Even within closed networks the HELiOS Internet Server can be used in a very efficient manner. For instance, it allows immediate mobile access to data and documents throughout the entire company, e.g. in the production department, warehouse, external service etc., without any special technical equipment being required.

PDM/PLM with HELiOS 5 / 24

HELiOS Spooler

The HELiOS Spooler is the automation platform for the processing of print, plot and conversion jobs by Servers or other automation tasks. The utilisation of the HELiOS Spooler offers the following advantages:

- Automatic processing of print/plot jobs with a multitude of configuration options, e.g. an automatic as-signing of printing devices according to format sizes.
- Automatic processing of conversion jobs, e.g. for an automatic creation of PDF documents. The availa-ble target formats vary depending on the utilized CAD base system.
- All jobs are handled centrally by the HELiOS Spooler, which spares the users at individual workstation a lot of work and avoids unnecessary disruptions of their daily work. A simultaneous running of multiple HELiOS Spoolers is also possible.
- Jobs can be controlled by a timer and prioritized.
- Current jobs, job statuses and job histories can be viewed as result lists. Individual jobs can be repeated at any time.

License Server

Before you can use HELiOS you need to get a license for the software. You have the following options:

Network Licenses If you choose network (server-controlled) licensing, the license will be directly locked to the hardware of the server that centrally manages the HELiOS licenses. These licenses can be used on any workstation in your network that is connected to this Server. But Network Licenses can even be used if the workstation has no network connection to the Server. For this to happen, a license can be temporarily provided via direct checkout from the License Server as a so-called "Commuter License".



 Standalone Licenses (local licenses) Here, the activation will be directly locked to the hardware of the workstation on which your HELiOS pro-gram is installed.

To be able to use Network Licenses, a License Server must have been installed.

The License Server carries out licensing in a multi-user environment and manages them. It also provided an overview of all licenses and regulates licensing requests of all users who wish to work with a HELiOS application.

PDM/PLM with HELiOS 7 / 24

System and Hardware Requirements

Important Notes!

Discontinuation of Windows® 7 and Windows® 8

Microsoft® has discontinued support for the Windows® 7 operating system in January 2020. For compatibility reasons, HiCAD 2020 SP2 and HELiOS 2020 SP2 were the last versions of our CAD or PDM system to support Windows® 7. HiCAD 2021 and HELiOS 2021 no longer run under Windows® 7, Windows® 8 and the corresponding server operating systems (Windows Server 2008 R2, Windows Server 2012 and older) are also no longer supported. If an attempt is made to install HiCAD 2021 or HELiOS 2021 on a computer with Windows® 7 or Windows® 8, a message appears.

Discontinuation of HELiOS 32-Bit and HiCAD Viewer 32-Bit

As of HELiOS 2022 (Version 2700.0), a 32-Bit version for HELiOS and the HiCAD Viewer will no longer be available. However, the interface to 32-Bit applications such as Office will still be possible and is not affected by the discontinuation of the 32-Bit installation of HELiOS.

Discontinuation of Oracle

As of HELiOS 2022 (Version 2700.0), Oracle will no longer be officially supported as a database system! Please migrate to a SQL Server as soon as possible.

Discontinuation of "old" interfaces

Before installing or updating, please check if your current interfaces are supported by HELiOS.

System Requirements for the HELiOS Database Server

The requirements with regard to the hardware primarily depend on the specifications given by the respective RDBMS supplier (Microsoft). Currently, following operating systems are supported:

	HELiOS 2023	HELIOS 2022	HELiOS 2021
Microsoft SQL Server 2022	√	×	×
Microsoft SQL Server 2019	√	√	√
Microsoft SQL Server 2017	✓	√	√
Microsoft SQL Server 2016	✓	√	√
Microsoft SQL Server 2014	√	√	√
Microsoft SQL Server 2012	√	√	√
Microsoft SQL Server 2008	×	×	×
Microsoft SQL Server 2005	×	×	×

In addition, the following minimum requirements should be guaranteed for the main memory and hard disk:

	HELiOS 2023	HELiOS 2022	HELiOS 2021
Main	Additionally at least 4 GB main memory.		
memory	With an increasing database size the working memory should be enlarged in order to guarantee optimal performance.		
Hard disk	Additionally at least 10 GB hard disk memory.		
	The actual demand depends on the size of the database.		



Please note:

- The use of virtual servers is essentially possible. Please consider to grant sufficient performance within the virtual environment.
- On the database server, HELiOS data base should be imported beforehand, for example via HELiOS Database Creator, so that clients can connect with the database.
- SQL Server Standard vs. SQL Server Express As of late, the productive use of SQL Server Express is possible. Please note that SQL Express has limited storage size (10 GB) for each data base and provides weaker performance than SQL Standard, especially on powerful hardware. If well-equipped hardware is used for the server (multiple processors and plenty of RAM), the SQL server thwarts the performance again. On regular desktop hardware the difference between SQL Express and SQL Standard is smaller due to the accordance of express limits and system.

PDM/PLM with HELiOS 9 / 24

System Requirements for the HELiOS Vault Server

The minimum requirements are as follows:

	HELiOS 2023	HELIOS 2022	HELiOS 2021
Processor (CPU)	64 Bit processor		
Main memory	Additionally at least 1 GB main	memory	
Hard disk	The required hard disk space depends on the volume of arising data use (files). A safety margin should be considered.		
Operating system	Microsoft Windows 10 or Microsoft Windows Server 2016 or higher		



Dlease note:

- If you work with only interfaces to HiCAD and/or Microsoft Office, the use of HELiOS Vault Servers is optional. Other interfaces must be used in conjunction with the HELiOS Vault Server.
- The needed hard disk space can also be distributed on multiple volumes.
- We recommend the use of RAIDs in order to ensure failsafe performance.

System Requirements for the HELiOS Client

The minimum requirements for the HELiOS Client are as follows:

	HELIOS 2023	HELIOS 2022	HELIOS 2021
Processor (CPU)	64 Bit processor		
Main memory	Additionally at least 2 GB main memory		
Hard disk	Additionally at least 2 GB free hard disk memory		
Operating system	Microsoft Windows 10 or Microsoft Windows Server 2016 or higher		

The interfaces that are available for the HELiOS Clientare listed in a Compatibility Matrix.



Please note:

- When interfacing the HELiOS Desktop with other applications, for instance with a CAD system or Office product, please consider the minimum requirements of each system manufacturer.
- If you want to use an integrated viewer, the hardware requirements of respective viewer manufacturer must be considered.
- Before you can use the HELiOS Client you require a HELiOS Database Server as well as an appropriately configurated ODBC connection.
 - Documents (in .pdf format) describing the installation procedure for the database system and the import and export of the database can be found here.

PDM/PLM with HFLiOS 11/24

Compatibility Matrix for Interfaced Applications (HELiOS)

Below you find a list of possible interfaces for the HELiOS Client:

	HELIOS 2023	HELIOS 2022	HELIOS 2021
Operating system			
Windows 11, 64 Bit	✓	(as of SP1)	×
Windows 10, 64 Bit	✓	✓	✓
Windows 8.1	×	×	×
Windows 8	×	×	×
Windows 7	×	×	×
Server Operating system			
Windows Server 2022	✓	(as of SP1)	×
Windows Server 2019	✓	√	✓
Windows Server 2016	✓	✓	√
CAD system			
HiCAD 2023	✓	×	×
HiCAD 2022	✓	✓	×
HiCAD 2021	✓	✓	✓
HiCAD 2020	×	✓	✓
HiCAD 2019	×	×	√
HiCAD 2018 or older	×	×	×
AutoCAD 2024	(as of SP2, Patch 1)	(as of SP2, Patch 3)	×
AutoCAD 2023	✓	(as of SP2, Patch 1)	(as of SP1, Patch 4)
AutoCAD 2022	✓	✓	(as of SP1)
AutoCAD 2021	√	√	√
AutoCAD 2020	✓	✓	✓
AutoCAD 2019	×	✓	√
AutoCAD 2018	×	×	√
AutoCAD 2017 or older	×	×	×

	HELiOS 2023	HELIOS 2022	HELiOS 2021
AutoCAD Mechanical 2024	(as of SP2, Patch 1)	(as of SP2, Patch 3)	×
AutoCAD Mechanical 2023	✓	(as of SP2, Patch 1)	(as of SP1, Patch 4)
AutoCAD Mechanical 2022	✓	✓	(as of SP1)
AutoCAD Mechanical 2021	✓	✓	✓
AutoCAD Mechanical 2020	✓	✓	✓
AutoCAD Mechanical 2019	×	✓	✓
AutoCAD Mechanical 2018	×	×	✓
Inventor 2024	(as of SP2, Patch 1)	(as of SP2, Patch 3)	×
Inventor 2023	(43 01 01 2, 1 4(011 1)	(as of SP2, Patch 1)	(as of SP1, Patch 4)
Inventor 2022	√	✓ (dd di di 2, i dteil 1)	(as of SP1)
*As of Inventor version 20	021.1 (or newer) can be	e used from HELiOS Version :	2502.3 or 2600.1. The
*As of Inventor version 20	021.1 (or newer) can be in Inventor described here.	e used from HELiOS Version :	2502.3 or 2600.1. The
*As of Inventor version 20 reason for this is the bug		e used from HELiOS Version :	2502.3 or 2600.1. The
*As of Inventor version 20		e used from HELiOS Version :	2502.3 or 2600.1. The
As of Inventor version 20 reason for this is the bug Inventor 2021 Inventor 2020		e used from HELiOS Version :	2502.3 or 2600.1. The
As of Inventor version 20 reason for this is the bug inventor 2021 Inventor 2020 Inventor 2019		e used from HELiOS Version	2502.3 or 2600.1. The
As of Inventor version 20 reason for this is the bug inventor 2021 Inventor 2020 Inventor 2019 Inventor 2018		e used from HELiOS Version :	2502.3 or 2600.1. The
As of Inventor version 20 reason for this is the bug inventor 2021 Inventor 2020 Inventor 2019 Inventor 2018 Inventor 2017 or older	in Inventor described here.	✓ ✓ ✓ ×	2502.3 or 2600.1. The
As of Inventor version 20 reason for this is the bug inventor 2021 Inventor 2020 Inventor 2019 Inventor 2018 Inventor 2017 or older Navisworks 2024		✓ ✓ ✓	✓ ✓ ✓ ✓
As of Inventor version 20 reason for this is the bug inventor 2021 Inventor 2020 Inventor 2019 Inventor 2018 Inventor 2017 or older Navisworks 2024 Navisworks 2023	in Inventor described here.	✓ ✓ ✓ ×	✓ ✓ ✓ ×
As of Inventor version 20 reason for this is the bug inventor 2021 Inventor 2020 Inventor 2019 Inventor 2018 Inventor 2017 or older Navisworks 2024 Navisworks 2023 Navisworks 2022	in Inventor described here.	✓ ✓ ✓ ×	✓ ✓ ✓ ✓ X X
As of Inventor version 20 reason for this is the bug inventor 2021 Inventor 2020 Inventor 2019 Inventor 2018 Inventor 2017 or older Navisworks 2024 Navisworks 2023 Navisworks 2022 Navisworks 2021	in Inventor described here.	✓ ✓ ✓ ×	✓ ✓ ✓ ✓ X X
As of Inventor version 20 reason for this is the bug Inventor 2021	in Inventor described here.	✓ ✓ ✓ ×	✓ ✓ ✓ ✓ X X

PDM/PLM with HELiOS 13 / 24

	HELIOS 2023	HELiOS 2022	HELIOS 2021
Navisworks 2017 or older	×	×	×
CAE-SYSTEM			
EPLAN Electric P8 2023	(as of Patch 3)	×	×
EPLAN Electric P8 2022	✓	(as of SP2, Patch 1)	(as of SP1, Patch 5)
EPLAN Electric P8 2.9	✓	✓	✓
EPLAN Electric P8 2.8	✓	✓	√
EPLAN Electric P8 2.7	✓	✓	✓
EPLAN Electric P8 2.6	✓	✓	✓
EPLAN Electric P8 2.5	✓	✓	✓
EPLAN Electric P8 2.4	✓	✓	✓
Zuken E3 2021	✓	(as of SP1)	×
Zuken E3 2020	✓	(as of SP1)	×
Zuken E3 2019	✓	✓	✓
OFFICE			
Office 2021	✓	(as of SP1)	×
Office 2019	✓	✓	✓
Office 2016	✓	✓	✓
Office 2013	✓	√	√
Office 2010 or older	×	×	×

The symbol does not always mean that the respective product is not compatible. It can also mean that the interactions between this product and the HELiOS Client have not been sufficiently tested by the ISD yet.

System Requirements for the HELiOS Internet Server

For the HELiOS Internet Server, similar system and hardware requirements as for the HELiOS Desktop apply:

	HELIOS 2023
Processor (CPU)	64 Bit processor
Main memory	Additionally at least 4 GB main memory
Hard disk	Additionally at least 2 GB free hard disk memory
Operating system	Microsoft Windows 10 or Microsoft Windows Server 2016 or higher
Others	As a prerequisite for the installation of a HELiOS Internet Server, a HELiOS Client must be installed beforehand.
	Operation via SSL (https) requires valid certificates for the corresponding web pages of the HELiOS Internet Server.


The Microsoft Internet Information Server (IIS), at least version 10.0 with ASP.NET 4.8 support, is also required. This is an integral part of Windows, but must be installed/activated separately before installing the HELiOS Internet Server.

Proceed as follows:

Choose **Control Panel > Programs and Features** and, at the top left of the window, select **Turn Windows features on or off**.

In the **Windows Features** dialogue window, blow Internet Information Services, expand the areas **Web Management Tools**, **World Wide Web Services > Application Development Features** and **Common HTTP Features**, and activate the checkboxes as shown below:

PDM/PLM with HELiOS 15 / 24





Please note:

- Besides IIS, HELiOS Client (HELiOS Desktop) must be installed.
- IIS URL Rewrite from https://www.iis.net/downloads/microsoft/url-rewrite must be installed.
- For the operation of the HELiOS Internet Server, a (sub)domain including a valid SSL certificate and port forwardings are required.
- To operate the HELiOS Internet Server, a number of website configurations in the Internet Information Server (IIS) are required. Parallel operation with other websites/products on the IIS is not recommended.

System Requirements for the HELiOS Spooler

Generally, the HELiOS Spooler is a 64 Bit application. The minimum requirements for the HELiOS Spooler are as follows:

	HELiOS 2023	HELiOS 2022	HELIOS 2021
Processor (CPU)	64 Bit processor		
Main memory	Additionally at least 2 GB main	memory.	
	systems used. This ensures the	dimensioned at least as large as nat all data to be processed by tems to the HELiOS Spooler) car	the HELiOS Spooler (which is
Hard disk	Additionally at least 4 GB free hard disk memory		
Operating system	Microsoft Windows 10 or Microsoft Windows Server 2016 or higher		



Dlease note:

- The HELiOS Spooler requires corresponding locally installed CAD, E-Tech or Office applications to execute the plot or conversion jobs. Please consider that you need appropriate licenses for the operation of these applications and that the hardware requirements of the respective system provider must be taken into account accordingly.
- The applications used by the HELiOS Spooler to process print and conversion jobs must be exclusively available to the Spooler and must not be used by other applications or HELiOS installations used simultaneously. Otherwise, job processing may be cancelled.
- In addition to the client operating systems for Windows, the above-mentioned server operating systems can also be used. Whether a server operating system must be used depends on the license conditions for the Microsoft operating system you are using. The number of permitted simultaneous device connections is decisive here. Windows 10 allows 20 simultaneous logins to the operating system. In this case, you must ensure that, in addition to the existing logins, there are sufficient free logins left that can be used by the respective print clients of the client computers.

PDM/PI M with HFI iOS 17/24

System Requirements for the License Server

The minimum requirement for running a license server is as follows:

	HELiOS 2023	HELiOS 2022	HELiOS 2021
Processor (CPU)	X86 or AMD64 Architecture.		
	Recommended: 2 GHz Processor		
Main memory	Additionally at least 1 GB main memory		
Hard disk	Additionally at least 2 GB free hard disk memory		
Operating system	Microsoft Windows 10 or Microsoft Windows Server 2016 or higher		

We use the Software Sentinel RMS© from gemalto© for licensing. The license server is in principal a 32 Bit application.



Please note:

- The license server need not be installed on a separate server or server operating system.
- A static IP address is required for the correct operation of a license server. When using a virtual server, a static MAC address is required.
 - The use of a cloud server is only possible if changes to the underlying hardware can be excluded by the cloud provider. This also includes that the provider does not move the virtual server to another physical machine.
- The license server must not be installed on the same computer with HELiOS Desktop, because both products share system information with regards to the licensing.
- Internet access is needed for the license server due to activation and deactivation.
- A Windows Server Core installation is not supported.

Operation in Virtual Environments

HELiOS Client

Generally, the HELiOS Client can be operated on Virtual Machines (VM). If you use integrated viewers, the hardware requirements of the respective viewer manufacturer must be considered.

The HELiOS Client can also be used as a terminal application.

HELiOS Spooler

Generally, the HELiOS Spooler can be operated on Virtual Machines (VM). However, limitations may occur with regard to simultaneously installed CAD system, electrical engineering software or Office applications.

With regard to graphics functionality, performance and integration of printers, too, limitations may occur in virtual environments.

License Server

The license management system based on Sentinel RMS© by the company gemalto© can, generally, also be used in virtual environments.

The use of a cloud server is only possible if changes to the underlying hardware can be excluded by the cloud provider. This also includes that the provider does not move the virtual server to another physical machine.

Network licenses on Virtual Machines (VM)

If you want to use/activate/deactivate the network licenses on virtual machines, please observe the following points:

- A static MAC address is required
- A static IP address is recommended or required when using Commuter Licenses
- Before copying or changing a virtual machine, deactivate the network licenses, since the UUID (Universal Unique IDentifier) of the VM will change due to the copying process, and cannot be deactivated afterwards any more. This also applies to the starting of the VM on a different host.

PDM/PLM with HELiOS 19 / 24

Multiple HELiOS Servers on One Computer

The following rules apply with regard to simultaneously installed, different HELiOS Server components on the same computer:

- The HELiOS Database Server, the HELiOS Vault Server and the ISD License Server can in principle be installed and operated together on one computer. However, the Database should not be located on the same RAID system as the user data of the HELiOS Vault Server. The Vault requires large hard disks, while the Database requires fast hard disks.
- Microsoft recommends not to install the MS SQL Server on a computer that is at the same time a domain controller
- The HELiOS Spooler with the integrated applications for conversion and printing should always be in-stalled on an own (if required, a virtual) machine.
- The same applies to the HELiOS Internet Server.
- None of the two above mentioned products should ever be combined with a Database Server, Vault Server or File Server.
- The HELiOS Vault Server can be installed together with the MS SQL Server on one machine, if the amount of data does not exceed a certain limit and the resources (especially RAM) on the machine are sufficient. A Vault Server can be moved subsequently to a different computer at any time.

Network Requirements

To avoid loss of performance we recommend the operation of HELiOS in a 1 GBit network or networks with an even higher bandwidth. Generally, the bandwidth affects the provision of the user data (e.g. CAD docu-ments) which need to be transmitted from the central storage directory or the HELiOS Vault Server, respec-tively, to the corresponding Clients.

Also, the latency of the connection between the HELiOS Clients and the HELiOS Database Server should be well below 5 ms; otherwise, the reactivity of the HELiOS Clients will be slowed down significantly.

PDM/PLM with HELiOS 21 / 24

Backup

You as a customer are responsible for regular data backup. The following data must be backed up:

- The HELiOS Database on the Database Server.
- The HELiOS Document storage directory or the Document and Management areas when using a HELiOS Vault Server. If multiple HELiOS Vault Servers are used (for a working across different locations), all HE-LiOS Vault Servers must be backed up.

If you use a HELiOS Vault Server please ensure that the time difference is as small as possible at the time of the backup of the HELiOS Database or the HELiOS Vault Server, respectively.

Legal notes

 $\ @$ 2023 ISD $\ @$ Software und Systeme GmbH. All rights reserved.

This User Guide and the software described herein are provided in conjunction with a license and may only be used or copied in accordance with the terms of the license. The contents of this User Guide solely serve the purpose of information; it may be modified without prior notice and may not be regarded as binding for the ISD Software und Systeme GmbH. The ISD Software und Systeme GmbH does not assume any responsibility for the correctness or accuracy of the information provided in this document. No part of this document may be reproduced, saved to databases or transferred in any other form without prior written permission by the ISD Software und Systeme GmbH, unless expressly allowed by virtue of the license agreement.

All mentioned products are trademarks or registered trademarks of their respective manufacturers and producers.

PDM/PLM with HELiOS 23 / 24





Germany

Headquarter Dortmund

ISD Software und Systeme GmbH Hauert 4 D-44227 Dortmund Tel. +49 231 9793-0 info@isdgroup.de

Sales office Hamburg

ISD Software und Systeme GmbH Strawinskystraße 2 D-25337 Elmshorn Tel. +49 4121 740980 hamburg@isdgroup.de

Sales office Nuremberg

ISD Software und Systeme GmbH Nordostpark 7 D-90411 Nuremberg Tel. +49 911 95173-0 nuernberg@isdgroup.de

International

ISD Austria

ISD Software und Systeme GmbH Hafenstraße 47-51 A-4020 Linz Tel. +43 732 21 04 22-0 info@isdgroup.at

ISD Benelux - Zwolle

ISD Benelux B.V. Grote Voort 293A NL-8041 BL Zwolle Tel. +31 73 6153-888 info@isdgroup.nl

ISD Switzerland

ISD Software und Systeme AG Rosenweg 2 CH-4500 Solothurn Tel. +41 32 624 13-40 info@isdgroup.ch

ISD USA - North Carolina

ISD Group USA Inc. 20808 N Main Street, Suite 101 USA-Cornelius NC 28031 Tel. +1 770 349 6321 info@isdgroup.us

www.isdgroup.com

Sales office Berlin

ISD Software und Systeme GmbH Paradiesstraße 208a D-12526 Berlin Tel. +49 30 634178-0 berlin@isdgroup.de

Sales office Hanover

ISD Software und Systeme GmbH Hamburger Allee 24 D-30161 Hanover Tel. +49 511 616803-40 hannover@isdgroup.de

Sales office Ulm

ISD Software und Systeme GmbH Wilhelmstraße 25 D-89073 Ulm Tel. +49 731 96855-0 ulm@isdgroup.de

ISD Benelux - Hertogenbosch

ISD Benelux B.V. Het Zuiderkruis 33 NL-5215 MV 's-Hertogenbosch Tel. +31 73 6153-888 info@isdgroup.nl

ISD France

ISD Group France SAS 10 -12 Boulevard Vivier Merle F-69393 Lyon Tel. +33 6 73 72 04 67 info@isdgroup.fr

ISD Switzerland

ISD Software und Systeme AG Rte du Jura 37 A, 4. Étage CH-1700 Fribourg Tel. +41 79 803 51 51 info@isdgroup.ch

ISD USA - Georgia

ISD Group USA Inc. 5126 South Royal Atlanta Drive USA-Tucker GA 30084 Tel. +1 770 349 6321 info@isdgroup.us

042023 HELIOS 2802

This document is generated automatically.

© 2023 ISD Software und Systeme GmbH